

This Service Manual supplement revises the information in Service Manual, Hood VN Group 82 PV776-TSP138123, 3/2000. The alteration is marked with a vertical line (|) in the margin.

Date	5.2001	Group	82 02	Page	1(1)
				Hood	
				VN	

Specification Change

The specifications on page 3 of Service Manual, Hood VN Group 82 have changed. The updated information is in the section titled "Hood Dimension and Alignment." Hood to cowl gap measurement is maximum 8mm.

Hood Torque Values

J-bracket mounting bolts	56 ± 10 Nm (41 ± 7 ft-lb)
Restraint cylinder mounting bolts	30 ± 4 Nm (22 ± 3 ft-lb)
Pivot bracket nuts	56 ± 10 Nm (41 ± 7 ft-lb)
Latch assembly mounting bolts	28 ± 5 Nm (21 ± 4 ft-lb)
Latch stud mounting bolts	28 ± 5 Nm (21 ± 4 ft-lb)
Latch arm mounting bolts	200 ± 33 Nm (148 ± 24 ft-lb)
Grille mounting screws	2 Nm (1.5 in-lb)

Hood Dimension & Alignment

Width across fenders (outside to outside)	2405 ± 3 mm (94.685 ± 0.1 in.)
Hood to cowl gap	maximum 8 mm greater than gap tool
Allowable difference between upper and lower gap	maximum 4 mm